



EZ FLAT A-100 is a matting/flatting paste for systems which Aromatic 100 is the preferred solvent such as lacquers and bake finishes.

Suggested Incorporating Techniques: **EZ FLAT** should always be mixed prior to use. In most cases, the **EZ FLAT** will be more viscous than the systems in which it will be used. Because of this, we recommend pre-mixing **EZ FLAT** first by diluting it with 5 to 10% solvent to be comparable with the viscosity of the system for incorporation, then added slowly into the batch while it is under agitation.

Typical Usage Levels: Add 5% by weight, to reduce gloss 70% at 60°. System solids and force cure vs. ambient will effect actual level required. For consistent results, agitate lightly before using (based on 35% vehicle solids).

Typical Properties:

Percentage Silica	15%
Percentage Vehicle	0%
Percentage Solvent	85% Aromatic 100
Weight per Gallon (lbs)	7.84
Specific Gravity	0.94
Flash Point F/C (closed cup)	110°/43°

Eagle Specialty Products · 2216 North Broadway · St. Louis, MO 63102
(314) 241-7771 · (888) 241-9802 · Fax: (314) 241-5356
www.espinc.us

Our data is based on laboratory tests which are believed to be accurate. However, all recommendations are made without warranty since the conditions of use are beyond the control of Eagle Specialty Products. We do not assume any liability of the product relative to performance or injury resulting from its use. Liability, if any, is limited to replacement product.