



## WAXES: SUPERSLIP 35

### AQUEOUS SYSTEMS

**SUPERSLIP 35** is a carnauba wax with a very low coefficient of friction that exhibits excellent mar and scuff resistance.

**Note:** The components of this product meet the following FDA Status 21CFR:

- Approved under 175.105
- Approved under 175.300 (extractives not to exceed 0.5 mg per square inch per extractive limits in 175.300(c))
- Approved under 175.320 (must meet extractive limits in 176.170(c))
- Approved under 176.170 (must meet extractive limitations in 176.170(c) and 176.180)

#### Typical Properties:

Wax	Carnauba
Percentage Solids	35%
Volatiles	Water
Average Particle Size	150nm
Specific Gravity	1.00
Viscosity (CPS)	<25 #1 Spindle @60RPM

Eagle Specialty Products · 2216 North Broadway · St. Louis, MO 63102  
(314) 241-7771 · (888) 241-9802 · Fax: (314) 241-5356  
[www.espinc.us](http://www.espinc.us)

Our data is based on laboratory tests which are believed to be accurate. However, all recommendations are made without warranty since the conditions of use are beyond the control of Eagle Specialty Products. We do not assume any liability of the product relative to performance or injury resulting from its use. Liability, if any, is limited to replacement product.